



ITEM	NAME	REQ	REF	ACCT NO
1	Bolt, 3/8-16x1-1/4 LG-Max Hd	9		
2	Bolt, 3/8-16x5/8 LG-Max Hd	3		
3	Collar	3	74647	02-134854
4	Post	1	74645	02-372405
5	Sign, stop	1	7010-1	02-496949
6	Approach sign	1	MW78317	02-487203
7	Washer, 3/8 Plain	3		19-751351
8	Washer, neoprene	3	9000-50	19-797172
9				
10				

- NOTES:
- Sign to be made from 6061-T6 aluminum alloy plate 0.081" thick.
 - Sign to be faced with Scotchlite or equal reflective material bonded to aluminum alloy plate. Colors to be as specified.
 - Sign to be single faced.
 - Proportions of letters to be in accordance with standard M/W plan 78010-A.
 - Bolts, nuts, and washers must be cadmium plated.
 - Paint post with black paint.
 - When installing post, coat all underground parts with no-oxide grease or equal.
 - Approach sign item 6 to be used in conjunction with stop sign located at braking distance in advance of stop sign per MW 4, Sec. 213.6.

74

REV	DATE	BY

SIGN 7010-1
 Face entire plate with No.2872
 Red high intensity Scotchlite mat'l.
 (47-723489)
 Letters to be No.2878 Silver high
 intensity Scotchlite (47-723000).

SHEET 1

CONRAIL CS-7010

STANDARD
STOP SIGN - PERMANENT

Approved *[Signature]*
 Chief Engineer CES

ISSUE DATE: 01.23.1980

REV.