



Type E Two-Unit Color Light Ground Signals

Type E Color Light Ground Signals

Note: See foreword and order information, page 220, at the beginning of this part.

Drawing references are shown for convenience in checking shipping lists and invoices.

Fig. No.	Name	Drawing Reference
Order by plate, figure number and name		
A	Type E Color-light Ground Signal Complete, consisting of two three-indication signal units equipped with $8\frac{3}{8}$ " doublet lenses and mounted on mast as shown	
A1	as above, except lower signal unit is a two-indication unit . . .	
B	Type E Color-light Ground Signal Complete, consisting of two three-indication signal units equipped with $8\frac{3}{8}$ " doublet lenses and mounted on mast supported on double door relay case as shown. Cable outlet and anchor bolts are not included. Specify shelving desired in relay case	
B1	as above, except lower signal unit is a two-indication unit . . .	
B2	same as Fig. B, except mast is supported on single door relay case shown on Plate E0915, Fig. A	
B3	same as Fig. B1, except mast is supported on single door relay case shown on Plate E0915, Fig. A	
C	Type E Color-light Ground Signal Complete, consisting of two three-indication signal units equipped with $8\frac{3}{8}$ " doublet lenses and mounted on mast supported on large double door relay case as shown. Cable outlet and anchor bolts are not included. Specify shelving desired in relay case	
C1	as above, except lower signal unit is a two-indication unit . . .	
C2	same as Fig. C, except mounted on a double relay and instrument case shown on Plate E0917, Fig. B	
C3	same as Fig. C1, except mounted on a double relay and instrument case shown on Plate E0917, Fig. A	
1	Type E Three-indication Signal Unit Complete. For details see Plates H2209 and H2211.	
2	Bracket Complete, with U bolts for mounting to 5" mast, includes flexible conduit connection	
3	Mast, 18', 8" long, of 5" and 6" pipe with A. R. A. base for mounting on foundation as shown in Fig. A	

(Continued on following page)

Type E Color Light Ground Signals

Drawing references are shown for convenience in checking shipping lists and invoices.

Fig. No.	Name	Drawing Reference
Order by plate, figure number and name		
4	Mast, 15', 1" long, of 5" pipe with base for mounting on relay case as shown in Fig. B	
5	Mast, 13', 2" long, of 5" pipe with base for mounting on relay case as shown in Fig. C	
6	Ladder Complete, includes hand rails, platforms, stays, clamps and bolts. Does not include foundation	
7	Relay Case Complete, 3', 6 ¹³ / ₁₆ " high, by 2', 5" wide, by 16" deep, with door on each side as shown, and with shelving as specified	
7a	as above, except with door on one side only	
8	Relay Case Complete, 5', 6 ³ / ₁₆ " high, by 2', 5 ¹ / ₂ " wide, by 16" deep with door on each side as shown, and with shelving as specified	
9	Cable Outlet Complete with conduit, length as specified	