



A

Combination Automatic and Train Order Signal

Color Light Signal

Combination Automatic and Train Order

Note: See foreword and order information, page 230, at the beginning of this part, also pages 42 and 43 of Bulletin No. 144.

If ladders with platforms and handrails are desired for this signal, same can be furnished, but this necessitates a special design and arrangement.

Combination Signals Complete of other types will be furnished when we are given full and complete information as to what is desired.

If a signal of a height other than shown is desired, same must be specified.

Drawing references are shown for convenience in checking shipping lists and invoices.

Fig. No.	Name	Drawing Reference
Order by plate, figure number and name		
A	Combination Automatic and Train Order Color-light Signal Complete, consisting of one three-indication Type G signal unit, one two and one single indication Type D signal units, equipped with 8 ³ / ₈ " doublet lenses and bracket mounted to mast as shown. Anchor bolts and ladder foundations are not included.....	
A1	as above, except with a three-indication Type D signal unit used in place of the three-indication Type G signal unit...	
1	Type G Three-indication Signal Unit Complete. For details see Plate H2309.....	
2	Type D Two-indication Signal Unit Complete. For details see Plates H2113 and H2115.....	
3	Type D Single-indication Signal Unit Complete without back-ground. For details see Plates H2113 and H2115.....	
4	Adapter Complete, as shown.....	51861
5	Bracket Complete, for mounting to a 5" mast, includes flexible conduit connection, and necessary bolts.....	
5a	as above, except without flexible conduit connection, but with fittings for Parkway cable.....	
6	Mast, of 5" pipe, height 21', 8" from top of foundation to top of pipe, drilled for mounting as shown. Includes pinnacle and A. R. A. base.....	
7	Ladder Complete, length as shown. Includes stays, clamps and bolts. Does not include foundation.....	310-38

(Continued on following page)