



Type SA Color-Light Bridge Signals

## Type SA Color-Light Bridge Signals

**Note:** See foreword and ordering information at the beginning of this part.

See Plate H2631 for signal unit with stepped lens and H2635 for signal unit with compound lens.

Drawing references are shown for convenience in checking shipping lists and invoices.

Fig. No.	Name	Drawing Reference
<b>Order by plate, figure number and name</b>		
A	Type SA Color-Light Bridge Signal Complete, consisting of one, three-indication signal unit with stepped or compound lenses <b>as specified</b> , and with base for mounting as shown. Number plates are not included and must be ordered separately. . . . .	
B	Type SA Color-Light Bridge Signal Complete, consisting of one, three-indication signal unit with stepped or compound lenses <b>as specified</b> and bracket mounted to short mast as shown. Specify length of mast desired. Number plates are not included and must be ordered separately. . . . .	
C	Type SA Color-Light Bridge Signal Complete, consisting of one, three-indication signal unit with stepped or compound lenses <b>as specified</b> and mounted on top of short mast as shown. Specify length of mast desired. Number plates are not included and must be ordered separately. . . . .	
1	Type SA Three-indication Signal Unit Complete, with stepped lens. For details and order references see Plate H2631. . . . .	53050-10
1a	as above, except with compound lens. For details and order references see Plate H2635. . . . .	53050-7
2	Hood, as shown, for use with 8 $\frac{3}{8}$ " dia. lens. . . . .	49127-19
2a	as above, except for use with 10 $\frac{1}{2}$ " dia. lens. . . . .	49127-20
3	Background, as shown, for use with 8 $\frac{3}{8}$ " dia. lens. . . . .	49162-25
3a	as above, except for use with 10 $\frac{1}{2}$ " dia. lens. . . . .	49162-24
4	Base, for mounting signal unit to bridge as shown in Fig. A. . . . .	53070-5
5	Hook Bolt, for fastening base, Fig. 4 to cord of bridge as shown. Includes nut and lock washer. Specify length. . . . .	635-41
6	Bolt, $\frac{3}{4}$ "-10 x 2 $\frac{1}{4}$ " sq. hd. with sq. nut, for fastening base, Fig. 4, to bridge as shown. . . . .	0617 35660 029

(Continued on following page)

## Type SA Color-Light Bridge Signals

Drawing references are shown for convenience in checking shipping lists and invoices.

Fig. No.	Name	Drawing Reference
<b>Order by plate, figure number and name</b>		
7	Number Plate, with number as specified, includes brackets and bolts for fastening to bridge. ....	
8	Mast, of 5" pipe, length as specified. ....	
9	Pinnacle Complete, as shown, for 5" mast. ....	56894 Gr. 2
10	Type SA Three-indication Signal Unit Complete, with stepped lens. For details and order references see Plate H2631. ....	53051-6
10a	as above, except with compound lens. For details and order references see Plate H2635. ....	53051-7
11	Base Complete, for 5" mast, for use as shown in Figs. B and C, when signal units are mounted above base. ....	43951-2 Gr. 1
11a	as above, except for use when mast extends through base for suspended signal units. ....	43951-2 Gr. 2
12	Socket Complete, for mounting signal unit to top of 5" dia. pipe (5 <sup>9</sup> / <sub>16</sub> " outside dia.) For details and order references see Plate H2631, Fig. J. ....	54732 Gr. 2