

MASTS, PINNACLES AND CABLE OUTLETS

## COLOR LIGHT SEARCHLIGHT SIGNAL DETAIL PARTS POSTS, CABLE OUTLETS, BASES, ETC.

Piece	Ref.	Description	Drawing Reference
149996	2	Mast, 5" Pipe drilled and tapped for Wire Outlets with A.R.A. Base for Ground Mounting as shown for One-Unit Searchlight Ground Signal Ref. A, Plate B-2800 and Two-Unit Searchlight Ground Signal Ref. B, Plate B-2805, 15' 10\frac{1}{2}" from Bottom of Base to Top of Mast.	B-9893-156
150883	2a	Mast, 5" Pipe drilled and tapped for Wire Outlets with A.R.A. Base for Ground Mounting for Two-Unit Searchlight Ground Signal Ref. A, Plate B-2805, 15' 101/2" from Bottom of Base to Top of Mast	B-9893-158
150901	2b	Mast, 5" Pipe drilled and tapped for Wire Outlets with A.R.A. Base for Ground Mounting for Three-Unit Searchlight Ground Signal Ref. A, Plate B-2810, 20' 11½" from Bottom of Base to Top of Mast.	B-9893-159
118996	2c	Mast, 5" Pipe, 15' 8" long (Without Base or Drilling for Refs. 2, 2a and 3)	B-10920-4
98648	2d	Mast, 5" Pipe, 20' 9" long (Without Base or Drilling for Ref. 2b)	B-10920-7
150900	3	Mast, 5" Pipe drilled and tapped for Wire Outlets with Base for Mounting on Instrument Case as shown for Three-Unit Searchlight Ground Signal Ref. B, Plate B-2810, 15' 10½" from Bottom of Base to Top of Mast	B-9893-159
149953	3a	Mast, 5" Pipe drilled and tapped for Wire Outlets with Base for Mounting on Instrument Case for One-Unit Searchlight Ground Signal Ref. D, Plate B-2800, 10' 10½" from Bottom of Base to Top of Mast.	B-9893-15
150121	3b	Mast, 5" Pipe drilled and tapped for Wire Outlets with Base for Mounting on Instrument Case for One-Unit Searchlight Ground Signal Ref. C, Plate B-2800 and Two-Unit Searchlight Ground Signal Ref. D, Plate B-2805, 12' 61/2" from Bot-	

## $\begin{array}{c} {\bf COLOR} \ {\bf LIGHT} \ {\bf SEARCHLIGHT} \ {\bf SIGNAL} \\ {\bf DETAIL} \ {\bf PARTS} \end{array}$

POSTS, CABLE OUTLETS, BASES, ETC.

(Continued)

Piece	Ref.	Description	Drawing Reference
150882	3c	Mast, 5" Pipe drilled and tapped for Wire Outlets with Base for Mounting on Instrument Case for Two-Unit Searchlight Ground Signal Ref. C, Plate B-2805, 10' 101/2" from Bottom of Base to Top of Mast	B-9893-154
146633	3d	Mast, 5" Casing drilled and tapped for Wire Outlets with Base for Mounting on Instrument Case for One-Unit Searchlight Ground Signal Ref. B, Plate B-2800, 10' 8" from Bottom of Base to Top of Mast.	B-9893-154
	3e	Mast, 5" Pipe drilled and tapped for Wire Outlets with Base for Mounting on Instrument Case for Three-Unit Searchlight Ground Signal Ref. Ba, Plate B-2810, 17' 6½" from Bottom of Base to Top of Mast.	B-9898
33097	3f	Mast, 5" Pipe, 10' 8" long (Without Base or Drilling for Refs. 3a and 3c)	B-10920-1
128052	3g	Mast, 5" Pipe, 12' 4" long (Without Base or Drilling for Ref. 3b)	B-10920-7
121002	3h	Mast, 5" Casing, 10' 51/2" long (Without Base or Drilling for Ref. 3d)	B-10920-7
	3j	Mast, 5" Pipe, 17' 4½" long (Without Base or Drilling for Ref. 3e)	B-10920
137792	4	Pinnacle with Set Screw	8121-44
87694	5	Base, for 5" Pipe for Refs. 3, 3a, 3b and 3c	C-7207-6
63263	5a	Base, for 5" Casing for Ref. 3d	C-7207-
21401	6	Base, A.R.A. for 5" Pipe for 2, 2a and 2b	C-7207-15
49059	6a	Base, A.R.A. for 5" Casing	C-7207-18
10276	7	Foundation Bolt, 1"x3' 0" with 1" Hex. Nut and Std. 1" Plate Washer	7913–54

# COLOR LIGHT SEARCHLIGHT SIGNAL DETAIL PARTS POSTS, CABLE OUTLETS, BASES, ETC.

(Continued)

Piece	Ref.	Description	Drawing Reference
147427	8	Pipe Cap with Two 3/8"-16x3/4" Hex. Hd. Tap Bolts (Cad. Pl.)	B-9931-5
152573	9	Cable Outlet for 11/2" Pipe, with Pipe, Lock Nut and Pipe Plug	B-10342-46
	10	Cable Outlet for 21/2" Pipe, with Pipe, Bushing and Lock Nut	B-10342-8
123274	11	Cap with 1" Pipe Tap	B-10342-46
45152	12	Pipe, 11/2" Galv. 161/2" long for Ref. 9	B-10342-3
63171	13	Clamp	B-10342-1
	14	Lock Nut, 11/2".	
	15	Bushing, 1½".	
	16	Bolt, ½"x2¾" Hex. Hd. and ½" Hex. Nut for attaching 13 to 11.	
	17	Pipe Plug 1".	
49658	18	Cap	B-10342-8
149005	19	Pipe, 21/2" Galv. 12" long for Ref. 10	B-11015-18
49659	20	Clamp	B-10342-8
	21	Bolt, ½"x3½" Hex. Hd. with ½" Hex. Nut for attaching 20 to 18.	
85591	22	Cable Clamp for 5" Pipe with two Bolts Ref. 22b	B-7501-8
85593	22a	Cable Clamp for 5" Casing with two Bolts Ref. 22b	B-7501-8
36830	22b	Bolt with ½" Hex. Nut	8280-81
3166	23	Wire Eye	7735–2
	24	Lock Nut 2½" for Ref. 10.	

# COLOR LIGHT SEARCHLIGHT SIGNAL DETAIL PARTS POSTS, CABLE OUTLETS, BASES, ETC.

(Continued)

Piece	Ref.	Description	Drawing Reference
	25	Bushing 2½" for Ref. 10.	1 300
153257	26	Wire Outlet, 1½" 90° M. I. (Galv.)	Name of the last
	27	Conduit, Double Strip Flexible, $1\frac{1}{2}$ " I. D.x2.060" O. D.x3' 0" long.	
	28	Conduit, Double Strip Flexible, $\frac{13}{16}$ I. D.x1.148" O. D.x2' 8" long.	
	29	Box Connector, 11/2" M. I. (Galv.)	
	29a	Box Connector, 3/4" M. I. (Galv )	