



Height $8\frac{3}{16}$ " , Width 4" , Depth 8"

Style "DN-22L" A.C.-D.C. Lightout Relay

The Style "DN-22L" Relay meets the demand for a relay to be used in series with differential double filament lamps.

This Relay is provided to operate on either A.C. or D.C. and is, therefore, suitable for A.C. installations where D.C. standby power is provided.

The Style "DN-22L" Relay consists of a Style "DN-22" Relay, similar to that shown on Plate E-4935, with special coils, and a rectifier mounted on a metal strap held in place by the bolts which fasten the backstrap to the cores. This rectifier is connected to the relay coil terminals. The relay is equipped with two front and two back low-voltage contacts. A tag is provided inside the relay listing the different lamps with which the relay may be used. The same relay may be used with any one of several different lamps.

For additional information on "DN-22" relays refer to Plate E-4935.

Style "DN-22L" A.C.-D.C. Lightout Relay

For details refer to Plate E-4978. Shock Absorber Bases (Ref. 56, Plate E-4978) or Wall Mounting Brackets (Ref. 57, Plate E-4978) are not furnished unless called for. Orders should specify resistance per pair of Coils. (See Ref. 8a, Plate E-5025).

Order by Plate, Piece, Reference and Abbreviated
Description Given in Heavy Face Type Only

| Piece | Ref. | Description | Drawing Reference |
|--------|------|--|-------------------|
| 196626 | A | Style "DN-22L" A.C.-D.C. Lightout Relay, Magnet Coils 0.185-Ohm Per Pair, with 2F and 2B dependent contacts (Contacts with silver to silver impregnated carbon front and silver to silver back). For use with any 8 or 10-Volt differential filament lamp where minor filament is rated at 3.5 Watts or with single filament lamps rated at 5 Watts. (If other lamps are to be used orders should so state). | C-9432-7 |
| 206447 | Aa | Style "DN-22L" A.C.-D.C. Lightout Relay, Magnet Coils 0.08-Ohm Per Pair, with 2F and 2B dependent contacts (Contacts with silver to silver impregnated carbon front and silver to silver back). For use with any approach lighted 8 or 10-Volt differential filament lamp where minor filament is rated at 6 watts. (If other lamps are to be used orders should so state)..... | C-9432-7 |
| 206894 | Ab | Style "DN-22L" A.C.-D.C. Lightout Relay, Magnet Coils 0.08-Ohm Per Pair, with 2F and 2B dependent contacts. (Contacts with silver to silver impregnated carbon front and silver to silver back). For use with any 8 or 10-Volt single filament lamps with ratings from 6 to 18 watts. (If other lamps are to be used orders should so state)..... | C-9432-7 |